



Premixed Grout

Tile Perfect™ Premixed Grout is a premium premixed grout that delivers highly durable, stain resistant grout joints. Unlike other premixed grouts, this unique, patented technology provides very high durability for residential use in intermittently wet as well as dry areas. It can also be used to grout over existing premixed or cementitious grout installations. Tile Perfect Premixed Grout is formulated with very fine particles of sand and may be used in grout joints as small as 1/16 inch. (Please see limitations regarding surfaces that might be sensitive to scratching).

- Grouts tile joints from 1/16 to 1/2 inch
- Highly stain resistant, no need to seal
- Grout is mold and mildew resistant
- Durable, wear resistant
- Water resistant, can use in showers
- Easy to use

Warranty

For details about our limited warranties, see your sales associate or www.hbfuller-cp/tp.

Product Specifications

Consistency	Color	Initial Cure	Final Cure	VOC	Compressive Strength
Paste	8 Colors	24 hours	7 days	36 g/L	799 psi

Limitations

Do not use with polished marble, metal tiles, most glass tiles*, or glass block. Do not use with travertine if the filling of the surface pits with grout is not desired. Certain tile surfaces may be stained when grouted with colored grout. Follow tile manufacturer recommendations or test. Use on grout joints from 1/16 in. up to 1/2 in. wide. Do not grout over existing epoxy grout installations. Maintain temperature range of 60°-100°F during use and drying. Freeze-thaw stable. If frozen, thaw completely and remix before using. Not for use in swimming pools or exterior applications. Do not add water. Do not seal grout.

*If sanded grout is appropriate with your glass tile, we recommend the use of Tile Perfect Premixed Grout.

Packaging

1/2 gallon plastic pail
Available colors:
Almond, Antique White, Bright White, DeLorean Gray, Light Buff, Pearl, Sandstone Beige, Summer Wheat

Coverage

Trowel Size	Approximate Coverage			
	Joint Width			
	1/16 in.	1/8 in.	1/4 in.	3/8 in.
4 in. x 4 in. x 1/8 in.	205 ft ²	103 ft ²		
6 in. x 6 in. x 1/4 in.	153.9 ft ²	76.9 ft ²	38.5 ft ²	25.6 ft ²
10 in. x 10 in. x 5/16 in.		102.7 ft ²	51.3 ft ²	34.2 ft ²
12 in. x 12 in. x 1/4 in.		153.9 ft ²	76.9 ft ²	51.3 ft ²

Surface Preparation

Area must be clean, dry, free of dirt and dust. Grout joint should be free of sealers.

Application Instructions

1. Grout no more than 10 sq. ft. at a time.
2. Press grout diagonally into joints holding float at a 45-degree angle. Make sure that joints are completely filled.
3. Remove all excess grout off tile by holding float at a 90-degree angle and drawing diagonally across tile.
4. For best results, wait 10 minutes before beginning clean up to allow the grout joint some time to firm up so it is not pulled out of the joint during clean up process. Do not wait longer than 40 minutes.
5. To clean, first soak sponge in cool clean water. Wring out most excess water, then pat the surface of the tile with the damp sponge to loosen the film. Next, rinse the sponge in water a second time and wring out excess water completely.
6. Use the damp sponge in a light, circular motion to smooth joints and clean film from the tile. Avoid using excessive amounts of water on the grout joints.
7. Turn sponge over to a clean side and draw diagonally across tiles to remove any remaining film.
8. For optimal results, follow these final clean-up steps: moisten a towel with clean water, wring out excess, then drag damp towel across surface diagonally. This will pick up remaining film.
9. If a light haze remains after cleaning, do not attempt to remove it with the sponge. Instead, leave the haze on the surface and remove the next day with a damp sponge. Haze will easily come off of most tile surfaces.
10. There is no need to seal Tile Perfect Premixed Grout.

Premixed Grout

GROUT

NOTE: If excess water is used in the sponge during clean up, minor cracks or pinholes can develop. If the grout is over-worked, it may appear to shrink down into joint. Should any of these things occur, simply apply a second coat to the affected areas. You must allow your initial application to cure for 24 hours prior to your second application.

Instruction For Use Over Premixed and Cement-Based Grout

To install, existing premixed or cementitious grout must be clean, sealer free, and 1/8 inch lower than tile surface. If not: Remove existing grout with a grout saw to at least 1/8 inch below the surface of the tile. Make sure the joint is free of all dust and debris, then apply grout per instructions above.

Set-up Time

Light foot traffic after 24 hours. Allow 7 days to achieve final cure which includes hardness and stain resistance. ALLOW 7 DAYS BEFORE EXPOSURE TO WATER.

Clean Up

Clean tools and hands with warm soapy water while grout is still wet.

Cautions

FIRST AID MEASURES: For eye contact, flush with water for 20 minutes. For skin contact, wash with soap and water. Get medical attention if irritation develops or persists. If inhaled, remove to fresh air. If swallowed, do not induce vomiting. Seek medical attention immediately. WARNING! This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. KEEP OUT OF REACH OF CHILDREN. For Medical Emergency Information, call 1-888-853-1758.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about and guidelines for the proper use and application of the covered Tile Perfect brand product(s) under normal environmental and working conditions. Because each project is different, H.B. Fuller Construction Products Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

Storage/Shelf Life

Store indoors in a cool, dry location. Keep away from excessive heat. Freeze/thaw stable to -10°F. If frozen, slowly bring material back to room temperature and mix per instructions.

Maximum of 1 year from date of manufacture in unopened package. Product good for 6 months after opening as long as bucket is re-sealed carefully and stored in a cool, dry, interior location and used within shelf life. Covering with plastic wrap directly on top of product prior to sealing container will help preserve freshness.

Customer and Technical Services

Customer support

Toll Free: 800-832-9002

Fax: 800-952-2368

Technical assistance

Information is available by calling the Technical Support Hotline.

Toll Free: 800-832-9023

Fax: 630-952-1235



H.B. Fuller Construction Products Inc.

1105 South Frontenac Street
Aurora, IL 60504-6451 U.S.A.
www.hbfuller-cp.com/tp