



Premixed Patch

SURFACE PREPARATION

The Tile Perfect™ Premixed Patch is water based and intended to repair minor imperfections to the substrate prior to the installation of the floor covering. It can be used to fill small voids (up to 1/4 in. deep per application) such as knot holes, nail marks on the floor, non-moving cracks, seams and joints. This product is designed to have floor covering installed on top of it and is not for use as a final wear layer. **Tile Perfect Premixed Patch is for porous substrates only.**

- Fast-setting – Floor coverings can be installed within 24 hours
- Convenient – Just stir and use
- Re-sealable container

Warranty

For details about our limited warranties, see your sales associate or www.hbfuller-cp/tp.

Suitable Substrates

- Interior/exterior concrete and masonry
- Interior wood surfaces
- Porous substrates only

Product Specifications

Weight	Working Time	Dry Time	VOC
Gallon - 14.8 lbs.	10-15 minutes at 75°F/50% RH	1/8 in. minimum 4 hours 1/4 in. minimum 16 hours	0 g/L

Limitations

Although this product is water resistant, the installation must be protected from any water or rain for a minimum 24-hour period. Single applications should not exceed 1/4 in. per application, with a total maximum of 1 in. Use over porous wood, concrete or masonry surfaces only. Do not use in areas subject to hydrostatic pressure. Do not use as a final wear layer or in standing water. Do not apply when temperature is below 50°F (10°C) or above 110°F (43°C). Do not allow patch to dry on any unintended surfaces (remove while wet). If sanding is required, ensure the area is well ventilated (i.e. open all windows and doors for cross ventilation). Wear a NIOSH approved air purifying respirator with dust/mist filter to protect your lungs against inhalation of airborne dust.

Packaging

1 Gallon

Coverage

Thickness	Approximate Coverage per Gallon
1/8 in. (0.32 cm)	12 ft ² (1.11 m ²)
1/4 in. (0.64 cm)	6 ft ² (0.56 m ²)

Surface Preparation

All surfaces must be structurally sound, clean, dry, and free from any oil, wax, grease, sealers, existing adhesives, waterproofing or curing compounds, or from contaminants that would interfere with bonding. Follow floor covering manufacturer's recommendations for allowable moisture vapor emissions.

Application Instructions

Mix well before using. Apply patch to the substrate with a putty knife. Press firmly into the area to be patched. Dampen the edge of your putty knife for ease of application. Apply up to a maximum 1/4 in. (0.64 cm) thickness per application. Do not overwork. Allow to dry between applications (See below for dry times).

Working time will vary based on thickness of application, substrate, temperature and relative humidity. Product will begin to skin over within 10-15 minutes at 75°F (24°C) / 50% RH.

Dry time at 1/8 in. thickness is a minimum of 4 hours and at 1/4 in. thickness a minimum of 16 hours. Humid conditions and low temperatures will increase dry times.

Clean Up

While product is still wet, clean hands and tools with warm, soapy water.

Cautions

FIRST AID MEASURES: In all cases, seek medical attention if symptoms develop or persist. EYES: Flush with water for 20 minutes. SKIN: Wash with soap and water. IF VAPORS INHALED: Remove to fresh air. IF SWALLOWED: Do not induce vomiting. WARNING! This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. KEEP OUT OF REACH OF CHILDREN. For Medical Emergency Information, call 1-888-853-1758.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about and guidelines for the proper use and application of the covered Tile Perfect brand product(s) under normal environmental and working conditions. Because each project is different, H.B. Fuller Construction Products Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

Premixed Patch

SURFACE PREPARATION

Storage/Shelf Life

Store in a cool dry interior location with lid tightly closed. Best to keep from freezing. If frozen, allow to thaw before use. Maximum shelf life of 1 year from date of manufacture in unopened package.

Customer and Technical Services

Customer support

Toll Free: 800-832-9002

Fax: 800-952-2368

Technical assistance

Information is available by calling the Technical Support Hotline.

Toll Free: 800-832-9023

Fax: 630-952-1235



H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504-6451 U.S.A.
www.hbfuller-cp.com/tp